

Design By Ramos & Bassols

The Spa wall or ceiling lamp projects a bright glare-free light thanks to the subtle fluted effect of its shade. The aluminium frame has a wide range of finishes to adapt to different interior designs.

Model Sheet

Finish	11 Black NCS S 8500-N
	25 Beige D1 NCS S 4005-Y50R
	23 Warm White NCS S 0502-Y50R

LED temperature color 2700 K / 3500 K

Dimming DALI / 1-10V / Casambi

Installation type Remote basic

Materials Diffuser: PMMA
Body: Aluminum
Ceiling rose: Aluminum

Light source 1 x LED STRIP 32,4W 600mA



LED CRI>90 3840 lm 119
2700 K / 3500 K

Driver 600 220~240 V V 50~60 Hz
HZ



Dimmable

LED

50-60Hz



1-10V

Application Ceiling Lamps

Packaging 1 Box
3.3 m x 0.1 m x 0.1 m
Gross weight 5.8
Net weight 3.6
Vol. 0.033

Lighting effect**Linear**

Linear lighting applications for functional and graphic illumination

Photometric Data

Go to vibia.com to get the photometric data for the different LED color temperatures.

Efficiency 60.77 lm/W

Coordinate System CG

Total Flux 1607.97 lm

Maximum Value 686.66 cd

All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty

Vibia Lighting, S.L.U.

Office / Oficina
Progrés 4-6. 08850 Gavà. Barcelona, Spain.

International T +34 934 796 971
Spain / Portugal T +34 934 796 970

customer.service@vibia.com
vibia.com