

Design By Ramos & Bassols

The Spa wall or ceiling lamp is suitable for damp areas. Its versatile system enables the luminaries to be placed in a line to illuminate up to two metres and a half of wall or ceiling space.

Model Sheet

Finish	25 Beige D1 NCS S 4005-Y50R
	11 Black NCS S 8500-N
	23 Warm White NCS S 0502-Y50R
LED temperature color	2700 K / 3500 K
Dimming	Casambi / 1-10V / DALI
Installation type	Remote basic / Surface Canopy

Materials	Diffuser: PMMA
	Body: Aluminum
	Ceiling rose: Aluminum
Light source	2 x LED STRIP 10,8W 600mA 
LED	CRI>90 3120 lm 144 2700 K / 3500 K
Driver	Constant Current 600 220~240 V V 50~60 Hz HZ
	 LED  

Application Ceiling Lamps

Packaging
1 Box
1.5 m x 0.1 m x 0.1 m
Gross weight 2.9
Net weight 1.8
Vol. 0.015

Lighting effect**Linear**

Linear lighting applications for functional and graphic illumination

Photometric Data

Go to vibia.com to get the photometric data for the different LED color temperatures.

Efficiency	60.79 lm/W
Coordinate System	CG
Total Flux	1286.38 lm
Maximum Value	549.33 cd

All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty

Vibia Lighting, S.L.U.

Office / Oficina
Progrés 4-6. 08850 Gavà. Barcelona, Spain.

International T +34 934 796 971
Spain / Portugal T +34 934 796 970

customer.service@vibia.com
vibia.com