











The Offset ceiling light is characterised by its linear design and easy surface installation. The Low-Glare High Efficiency linear model allows for highly energy efficient installations and minimal glare. The structure is aluminium with powerful Led light strips, a versatile fitting offering static and Tunable White lighting options to customise spaces according to individual project requirements. A stylish and sustainable solution for a warm and light filled ambience.

Model Sheet

Finish	 24 Beige M1 NCS S 2005-Y50R
	 11 Black NCS S 8500-N
	 23 Warm White NCS S 0502-Y50R
LED temperature color	2700 K / 3000 K / 3500 K / Tunable White
Dimming	PROTOPIXEL / CASAMBI / PUSH / DALI
Installation type	Surface

Materials	Box: Aluminum Diffuser: PE- Polyethylene Frame: PC- Polycarbonate
Light source	1 x LED STRIP 13,7W 650mA 
LED	CRI>90 1674 lm 122,63 2700 K / 3000 K / 3500 K / Tunable White
Driver	Constant Current 650 220~240 V V 50~60 Hz HZ
Application	  Dimmable 
	  
Packaging	Box Gross weigth Net weigth

Lighting effect

Linear High Efficiency - Low Glare

High energy efficiency and low glare levels
UGR<19 for linear light applications

Photometric Data

All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty