







The Offset ceiling light, characterised by its double accent light points, manages to integrate within any space in a balanced way thanks to its simple surface installation. Its versatility is increased by combining several units, providing a wide range of creative options for designing unique contemporary compositions for ceilings. This is made possible by the solid aluminium casing that provides durability and an attractive angular design.

Model Sheet

Finish	 23 Warm White NCS S 0502-Y50R
	 90 Black NCS S 8500N
	 24 Beige M1 NCS S 2005-Y50R
LED temperature color	2700 K / 3000 K / 3500 K
Dimming	CASAMBI / PUSH / PROTOPIXEL / DALI
Installation type	Surface
Materials	Box: Aluminum Diffuser: PC- Polycarbonate
Light source	2 x undefined
LED	CRI>90 570 lm 98.3 2700 K / 3000 K / 3500 K
Driver	Constant Current 250 120~240 V V 50~60 Hz HZ
	  Dimmable LED
	IP20 50-60Hz 120-240V  PUSH
Application	Ceiling Lamps
Packaging	Box  Gross weigth Net weigth

**Lighting effect**

**Accent**

Narrow: Angles less than 20°. Suitable for generating high contrasts or projections at far distances. Medium: Angles between 20° and 40°. Suitable for generating medium contrasts or projections at medium distances. Wide: Angles greater than 40°. Suitable for generating moderate contrasts or projections at near distances

**Photometric Data**

All of our products come with a five-year warranty. Check our legal terms at [www.vibia.com/warranty](http://www.vibia.com/warranty)