













The Offset ceiling model with its three accent light points can be elegantly integrated with any space thanks to its uncomplicated surface installation. The versatility is increased by combining several units, offering a vast range of creative possibilities for creating exclusive ceiling compositions. This is made possible by the solid aluminium casing that guarantees durability and a refined aesthetic.

Model Sheet

Finish	 23 Warm White NCS S 0502-Y50R
	 11 Black NCS S 8500-N
	 24 Beige M1 NCS S 2005-Y50R
LED temperature color	2700 K / 3000 K / 3500 K
Dimming	CASAMBI / PUSH / DALI / PROTOPIXEL
Installation type	Surface
Materials	Box: Aluminum Optics: PMMA- Methacrylate
Light source	3 x undefined 
LED	CRI>90 855 lm 98,3 2700 K / 3000 K / 3500 K
Driver	Constant Current 250 120~240 V V 50~60 Hz HZ
Application	   
	   
Packaging	Box  Gross weigth Net weigth

Lighting effect

**Accent**  
Narrow: Angles less than 20°. Suitable for generating high contrasts or projections at far distances. Medium: Angles between 20° and 40°. Suitable for generating medium contrasts or projections at medium distances. Wide: Angles greater than 40°. Suitable for generating moderate contrasts or projections at near distances

Photometric Data

Efficiency	98,3
Total Flux	855

All of our products come with a five-year warranty. Check our legal terms at [www.vibia.com/warranty](http://www.vibia.com/warranty)