

Bind solo



6634


VIBIA



Bind Solo provides downwards accent lighting via a surfaced mounted fitting. The angle of aperture allows for the creation of contrasts over medium distances.

Model Sheet



Finish	 04 Black NCS S 8500N
	 24 Beige M1 test ral
LED temperature color	2700 K / 3000 K / 3500 K
Dimming	NO DRIVER / PUSH DALI / CASAMBI / On/Off
Installation type	Remote driver Built-in Micro

Materials	Body: Aluminum Optics: PC- Polycarbonate
Light source	1 x LED 4.3W 250 mA 
LED	CRI>90 451 lm 104,9 2700 K / 3000 K / 3500 K
Driver	Constant Current 250 220~240 V V 50~60 Hz HZ

  IP20 50-60Hz

Application	Ceiling Lamps
Packaging	1 Box 0.15 m x 0.15 m x 0.075 m Gross weight 0.67 Net weight 0.19 Vol. 0.0016

Lighting effect

Accent

Narrow: Angles less than 20°. Suitable for generating high contrasts or projections at far distances. Medium: Angles between 20° and 40°. Suitable for generating medium contrasts or projections at medium distances. Wide: Angles greater than 40°. Suitable for generating moderate contrasts or projections at near distances

Photometric Data

All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty

Vibia Lighting, S.L.U.

Office / Oficina
Progrés 4-6. 08850 Gavà. Barcelona, Spain.

International T +34 934 796 971
Spain / Portugal T +34 934 796 970

customer.service@vibia.com
vibia.com